

T5

For excavators 4.0-6.0 ton

HYDRAULIC MULCHERS

T5 105



HF2
Ø max 5 cm

standard equipment










H1C
Ø max 4 cm



KC1
Ø max 3 cm



Model	 (ton)	 (cm)	 (LxAxH cm)	 Kg	Motor displacement	 (L/min)	 bar (min-max)	Transmission	Rotor	
T5 105	4.0-6.0	105	130x60x40	190	16-22	40-60	170-220	direct	helical	16

TECHNICAL FEATURES AND STANDARD EQUIPMENT


- Direct transmission.
- Internally reinforced with double metal sheet.
- Feeler roller adjustable on 3 positions to change the height of the cut.
- Helicoidal rotor with austempered hammers or blade interchangeable.
- Protective cover for motor.
- Inside rotor supports with labyrinth for the protection of the bearings by the impurities.
- Double row spherical adjustable bearings of 1st quality.
- Valves block complete with priority valve for adjusting oil flow, anti-shock valve (pressure relief valve), anti-cavitation.
- Gear motor.
- Accident prevention rubber protections according to EC directives.

ACCESSORIES

- 1 - Mounting hitch & pins.
- 2 - Kit hoses Lg. 2 meters.
- 3 - Front chain protection.
- 4 - Self-levelling support (+40kg).
- 5 - Valves block deduction, only anticavitation.
- 6 - Motor 22cc group 3



1



3



4