

# T7

For excavators 5.0-8.0 ton













**MZ**



**HF3**  
Ø max 8 cm  
**STANDARD  
EQUIPMENT**



**KF3**  
Ø max 6 cm

		<b>T7 105</b>	<b>T7 125</b>
	<b>ton</b>	5.0-8.0	6.0-8.0
	<b>cm/inch</b>	105 42	125 50
	<b>cm/inch</b>	125x75x50 50x30x20	145x75x50 58x30x20
	<b>kg/lbs</b>	220 485	250 551
	<b>cc</b>	22-27-34	22-27-34
	<b>oil - L/min (gal/min)</b>	60-70-80 16-19-22	60-70-80 16-19-22
	<b>bar/psi (min-max)</b>	200-220 2.900-3.200	200-220 2.900-3.200
	<b>transmission</b>	direct	direct
	<b>rotor diameter cm/inch</b>	36 14	36 14
		16	20




### Technical features and standard equipment

- Direct transmission
- Internally reinforced with double metal sheet
- Feeler roller adjustable on 3 positions to change the height of the cut
- Helicoidal rotor with austempered hammers or blade interchangeable
- Protective cover for motor
- Inside rotor supports with labyrinth for the protection of the bearings from the impurities
- Double row spherical adjustable bearings of 1<sup>st</sup> quality
- Valves block complete with priority valve for adjusting oil flow, anti-shock valve (pressure relief valve), anti-cavitation
- Cast iron gear motor
- Accident prevention rubber protections according to EC directives

### Accessories

- Mounting hitch (pins version)
- Pins kit
- Quick hitch
- Hoses kit Lg. 2 meters
- Self-levelling support (+40kg)
- Hydraulic rotation device (no self-levelling support)
- Valves block deduction, only anticavitation

### Cast iron hydraulic gear motor range

	<b>ton</b>	5-7	7-8	8-9
	<b>cc</b>	22	27	34
	<b>oil - L/min gal/min</b>	60 16	70 19	80 22