

TE1

HYDRAULIC MULCHER TRINCIATRICE IDRAULICA



WATCH IT IN ACTION
GUARDA IN AZIONE

FEATURES

- Mulcher designed for cleaning grass and shrubs.
- Direct transmission.
- Symmetrical shearing head for quick excavator rotation.
- Protective cover for motor.
- Valves block complete with priority valve for adjusting oil flow, anti-shock valve (pressure relief valve), anti-cavitation and self-draining.
- "Casappa" aluminium group 2 gear motor.
- Accident prevention rubber protections according to EC directives

Upon request:

- custom-made mounting bracket;
- hoses.

CARATTERISTICHE

- Trinciatrice progettata per la pulizia di erba e piccoli arbusti.
- Trasmissione diretta.
- Trinciatrice simmetrica per un taglio più veloce con la rotazione dell'escavatore.
- Protezione carter motore.
- Blocco valvole comprensivo di valvola prioritaria per regolazione della portata olio, antiurto (valvola di max pressione), anticavitazione e autodrenante.
- Motore gruppo 2 in alluminio "Casappa".
- Protezioni antinfortunistiche in gomma a norma CE.

Su richiesta:

- sella di attacco, disponibile su misura;
- fornitura di tubi.

TECHNICAL INFORMATION

CARATTERISTICHE TECNICHE



MADE IN ITALY
OMEF
FORESTRY EQUIPMENT MANUFACTURER

Rotor
Rotore

K/M



MAZHF1
Ø max 3 cm



CLTKF1
Ø max 2 cm



MODELLO MODEL	tons	cm/inch	LxAxH cm/inch	KG kg/lbs	CILINDRATA MOTORE ENGINE DISPLACEMENT	OIL l/min - gpm	bar - psi (min-max)		
TE1.1-60K/M	1 - 3	60 24	85x50x35 34x20x14	70 154	8 - 11	20-30 6-8	170-220 2500-3200	direct diretta	12
TE2.1-80K/M	2 - 3	80 32	100x50x35 40x20x14	80 176	8 - 11	30-40 8-11	170-220 2500-3200	direct diretta	14

Hydraulic gear motor range
Scelta motore idraulico a ingranaggi

ton	1 - 2	2 - 3
CILINDRATA MOTORE ENGINE DISPLACEMENT cc	8	11
l/min gpm	20 6	30 8