

HYDRAULIC MULCHER TRINCIATRICE IDRAULICA



WATCH IT IN ACTION
GUARDA IN AZIONE

FEATURES

- Mulcher designed for cleaning grass and shrubs.
- Feeler roller adjustable on 3 positions to change the height of the cut.
- Helicoidal rotor with tempered hammers or interchangeable blades.
- Protective cover for motor.
- Valves block complete with priority valve for adjusting oil flow, anti-shock valve (pressure relief valve), anti-cavitation and self-draining.
- "Casappa" aluminium group 2 gear motor.
- Accident prevention rubber protections according to EC directives

Upon request:

- custom-made mounting bracket;
- hoses.

CARATTERISTICHE

- Trinciatrice progettata per la pulizia di erba e arbusti.
- Rullo di appoggio regolabile su 3 posizioni per variare l'altezza di taglio
- Rotore elicoidale con mazze bonificate o coltelli intercambiabili.
- Protezione carter motore.
- Blocco valvole comprensivo di valvola prioritaria per regolazione della portata olio, antiurto (valvola di max pressione), anticavitazione e autodrenante.
- Motore gruppo 2 in alluminio "Casappa".
- Protezioni antinfortunistiche in gomma a norma CE.

Su richiesta:

- sella di attacco, disponibile su misura;
- fornitura di tubi.

TECHNICAL INFORMATION

CARATTERISTICHE TECNICHE



MADE IN ITALY
OMEF
FORESTRY EQUIPMENT MANUFACTURER

Rotor
Rotore

K/M



MAZHF2
Ø max 5 cm



CLTKC1
Ø max 3 cm



MODELLO MODEL	 tons	 cm/inch	 LxAxH cm/inch	 kg/lbs	CILINDRATA MOTORE ENGINE DISPLACEMENT	 l/min - gpm	 bar - psi (min-max)		
TE1.3-70K/M	1,5 - 5	70 28	95x55x45 38x22x18	130 287	8 - 11 - 16	20-30-40 6-8-11	170-220 2500-3200	direct diretta	10
TE2.3-90K/M	2 - 5	90 36	115x55x45 46x22x18	150 331	11 - 16	30-40 8-11	170-220 2500-3200	direct diretta	14

Hydraulic gear motor range
Scelta motore idraulico a ingranaggi

 ton	1,5 - 2	2 - 3,5	3,5 - 5
CILINDRATA MOTORE ENGINE DISPLACEMENT cc	8	11	16
 l/min gpm	20 6	30 8	40 11