

TE7

HYDRAULIC MULCHER TRINCIATRICE IDRAULICA



**WATCH IT IN ACTION
GUARDA IN AZIONE**

FEATURES

- Mulcher designed for cleaning grass and shrubs over large areas.
- Direct transmission.
- Feeler roller adjustable on 3 positions to change the height of the cut.
- Helicoidal rotor with austempered hammers or interchangeable blade.
- Protective cover for motor.
- Valves block complete with priority valve for adjusting oil flow, anti-shock valve (pressure relief valve), anti-cavitation and self-draining.
- "Casappa" aluminium group 3 gear motor.
- Accident prevention rubber protections according to EC directives

Upon request:

- custom-made mounting bracket;
- hoses.

CARATTERISTICHE

- Trinciatrice progettata per la pulizia di erba e arbusti su ampie superfici.
- Trasmissione diretta.
- Rullo di appoggio regolabile su 3 posizioni per variare l'altezza di taglio.
- Rotore elicoidale con mazze bonificate o coltelli intercambiabili.
- Protezione carter motore.
- Blocco valvole comprensivo di valvola prioritaria per regolazione della portata olio, antiurto (valvola di max pressione), anticavitazione e autodrenante.
- Motore gruppo 3 in ghisa "Casappa".
- Protezioni antinfortunistiche in gomma a norma CE.

Su richiesta:

- sella di attacco, disponibile su misura;
- fornitura di tubi.

TECHNICAL INFORMATION

CARATTERISTICHE TECNICHE



MADE IN ITALY
OMEF
FORESTRY EQUIPMENT MANUFACTURER

Rotor
Rotore

K/M



MAZHF3
Ø max 8 cm



CLTKF3
Ø max 6 cm



MODELLO MODEL	tons	cm/inch	LxHxW cm/inch	KG kg/lbs	CILINDRATA MOTORE ENGINE DISPLACEMENT	OIL l/min - gpm	bar - psi (min-max)	direct	20
TE1.7-125K/M	5 - 8	125 50	145x75x50 58x30x20	250 551	22 - 27 - 34	60-70-80 16-19-22	200-220 2900-3200	direct diretta	20

Hydraulic gear motor range
Scelta motore idraulico a ingranaggi

ton	5 - 7	7 - 8	8 - 9
CILINDRATA MOTORE ENGINE DISPLACEMENT cc	22	27	34
l/min gpm	60 16	70 19	80 22