

TE9

HYDRAULIC MULCHER TRINCIATRICE IDRAULICA



**WATCH IT IN ACTION
GUARDA IN AZIONE**

FEATURES

- Powerful and versatile mulcher suitable for cleaning shrubs and plants.
- K/M helical forestal rotor with 360° rotating hammers.
- MSFS swinging hammer flail mulcher with 360° rotating hammers.
- DF fixed teeth forestry mulcher.
- 3 toothed high-performance V-belts transmission.
- Internally reinforced double-case body
- Protective belts cover.
- Symmetrical shearing head for quick excavator rotation.
- Adjustable hood, fully openable for higher cutting capacity.
- Valves block complete with priority valve for adjusting oil flow, anti-shock valve (pressure relief valve), anti-cavitation and self-draining.
- "Casappa" group 3 cast iron gear motor.
- Accident prevention rubber protections according to EC directives.

Upon request:

- custom-made mounting bracket;
- hoses.

CARATTERISTICHE

- Trinciatrice progettata per la pulizia di erba e arbusti su ampie superfici.
- K/M rotore a mazze elicoidale con mazze bonificate e coltelli intercambiabili.
- MSFS rotore a mazze rotanti a scomparsa.
- DF rotore forestale a denti fissi.
- Trasmissione a 3 cinghie trapezoidali dentate.
- Cofanatura interna.
- Protezione carter cinghie.
- Trinciatrice simmetrica con bocche d'ingresso identiche in entrata e in uscita.
- Frontalini porta catene di protezione regolabili in altezza.
- Blocco valvole comprensivo di valvola prioritaria per regolazione della portata olio, antiurto (valvola di max pressione), anticavitazione e autodrenante.
- Motore gruppo 3 in ghisa "Casappa".
- Protezioni antinfortunistiche in gomma a norma CE.

Su richiesta:

- sella di attacco, disponibile su misura;
- fornitura di tubi.

TECHNICAL INFORMATION

CARATTERISTICHE TECNICHE



Cast iron hydraulic gear motor range
Scelta motore idraulico a ingranaggi

ton	3 - 4	5 - 6	6 - 7	7 - 8	8 - 10	10 - 12
CILINDRATA MOTORE ENGINE DISPLACEMENT	16	22	27	34	43	51
l/min gpm	30 8	40 11	50 14	60 16	80 22	100 28

Rotor Rotore

K/M



MAZHF3

Ø max 8 cm



CLTKF3

Ø max 6 cm



MODELLO MODEL	tons	cm/inch	LxAxH cm/inch	KG kg/lbs	CILINDRATA MOTORE ENGINE DISPLACEMENT	l/min - gpm	bar - psi (min-max)		
TE1.9-70K/M	3 - 5	70 28	85x80x60 34x32x24	180 397	16	30 8	170-220 2500-3200	3	10
TE2.9-90K/M	4,5 - 8	90 36	105x80x60 42x32x24	260 573	22 - 27 - 34	40-50-60 11-14-16	170-220 2500-3200	3	14

Rotor Rotore

MSFS



MAZHF17

Ø max 12 cm



MODELLO MODEL	tons	cm/inch	LxAxH cm/inch	KG kg/lbs	CILINDRATA MOTORE ENGINE DISPLACEMENT	l/min - gpm	bar - psi (min-max)		
TE1.9-70MSFS	5 - 8	70 28	85x80x60 34x32x24	290 640	22-27-34- 44-51	40-50-60- 80-100 11-14-16- 22-28	200-220 2900-3200	3	12
TE2.9-90MSFS	6 - 8	90 36	105x80x60 42x32x24	360 792	22-27-34- 43-51	40-50-60- 80-100 11-14-16- 22-28	200-220 2900-3200	3	18

Rotor Rotore

DF



DFHF14P

Ø max 25 cm



DFHF15

Ø max 20 cm



MODELLO MODEL	tons	cm/inch	LxAxH cm/inch	KG kg/lbs	CILINDRATA MOTORE ENGINE DISPLACEMENT	l/min - gpm	bar - psi (min-max)		
TE1.9-70DF	5 - 12	70 28	85x80x60 34x32x24	340 750	22-27-34- 44-51	40-50-60- 80-100 11-14-16- 22-28	200-220 2900-3200	3	21
TE2.9-90DF	6 - 12	90 36	105x80x60 42x32x24	400 882	27-34- 43-51	50-60- 80-100 14-16- 22-28	200-220 2900-3200	3	24