
FORESTRY MULCHERS
AGRICULTURE MULCHERS
HYDRAULIC MULCHERS



# E4 RANGE E4-100 E4-120 E4-140





### **E4 RANGE**

FORESTRY MULCHERS AGRICULTURE MULCHERS HYDRAULIC MULCHERS

Flail-Tec is a dynamic and innovative company specialising in manufacturing heads for excavators, tractors, skid steers, and tracked vehicles tailored for the forestry and agricultural sectors. With our continuously growing product line and unwavering dedication to quality, productivity, and durability, our goal is to deliver world-class industry solutions to our customers.

#### **E4** Range Key Features:

- PowerPulse variable torque technology as standard 60/80cc hydraulic piston motor with anticavitation valve and PRV. Suitable for auxiliary flows of 100l/min to 2001/min and up to 350 bar
- Hydraulically adjustable Hardox lined door
- Replaceable inner Hardox liners with counter cutters
- Extremely robust full length double skinned design
- Fully enclosed motor with multiple hatches for easy access
- Customised hitch bracket
- Conveniently positioned grease nipple locations
- Heavy duty skids with two height options
- Heavy duty SKF bearings
- Sealed body projects from dirt and dust buildup
- Projectile protection double lavered chains
- Belt driven transmission system

#### Options available:

Planer tooth rotor with bite **limiter** - This extremely productive and easy to maintain configuration controls the tooth cutting depth for a more consistent chip.



Carbide teeth rotor - Highly durable teeth are more forgiving when dealing with rocky terrains, these teeth can last 3-5 times longer than steel.



**Hammer Flail** - Highly effective against heavier tree sapling, hedges, and dense overgrowth. The flail offers protection against load spikes, as when a flail strikes an immovable object, it simply bounces off protecting the mulcher and reducing thrown objects which can cause damage.

Thumb bracket for moving and manipulating material to be mulched.

Multiple tooth and rotor options.



Fixed tooth or flail option available

At Flail-Tec, our mission is to empower forestry and agricultural professionals with cutting-edge mulching technology that enhances productivity, minimizes environmental impact, and promotes sustainable land management practices.









Hardox liners with

**WEARPARTS** 

counter cutters



A simple solution that automatically increases the motor displacement in heavy ad applications, increasin torque and reducing system pressure.

## **E4 RANGE**



FORESTRY MULCHERS AGRICULTURE MULCHERS HYDRAULIC MULCHERS

#### **TECHNICAL SPECIFICATION**

Model Name	E3-100	E4-120	E4-140
Excavator weight (t)	13-20	14-20	16-20
Flow rate (L/min)	100-170	120-200	120-200
Pressure (bar)	180-350	180-350	180-350
Working Width (mm)	1000	1200	1400
Weight (kg)*	1045	1155	1275
Rotor Cutting Diameter (mm)	450	450	450
Number of Carbide Teeth	30	36	42
Number of Planer Teeth	12	16	19
Number of Hammer Flails	16	20	24

<sup>\*</sup>Weight data in table excludes hitch and is with hammer flail rotor. Contact Flail-Tec for other rotor option weights. Technical data in table may be altered without prior notice.

57 Ballynasaggart Road Dungannon Co Tyrone Northern Ireland BT70 2AZ