

Flailbot Supreme Stage V / T4 Final

The flagship model – enjoy ultimate horse power with the 75hp engine giving maximum power and control to the operators finger tips.

The Flailbot Supreme Stage V / T4 Final is the most powerful model in the range. Fitted with a Perkins Stage V tier 4 Final engine producing over 270 NM of torque it also comes with hydraulic adjustable track width and auto track tension system as standard.

Key Features

- 4 Cylinder 75hp Stage V / T4 Final Perkins engine
- Hydraulically adjustable track frame
- 39 litre (10 USG) fuel tank capacity
- 150m (492') working range



**Want to know more about the
Flailbot Supreme Stage V / T4 Final**

Scan the QR code with a smart phone or
tablet to instantly view the page.





Clearing areas of dense vegetation

Cutting through heavy undergrowth to allow easy access.



Rear protection

Fitted with rear protection bar and towing anchor point.

Flailbot Supreme Stage V / T4 Final Weights & Dimensions

Engine Size / Capacity
75hp /
2.2 Litres / 134.2 in³

Flailbot with Oil & Fuel
2200 kg / 4,850 lbs

1650 Flail Head
450 kg / 992 lbs

Features & Specification

Flailbot	Supreme Stage V / T4 Final (75hp)
Operation	
Max Slope	55°
Transmission	Hydrostatic
Speed	0-7 km/h
Weight	2200kg / 4,850 lbs
Engine	
Brand / Make	Perkins, Tier 4 Final
Model	4 Cylinders, Diesel, Direct Injection
Engine Size	2.2 Litres / 134.2 in ³
Power	55 kW / 75 Cv
Max Torque	270 Nm / 199 ft-lb @ 1800 rpm
Intake	Turbocharged aftercooled
Cooling	Liquid
Air Filter	Dry
Diesel Tank Capacity	39 Litres / 10.3 USG
Engine Oil Quantity	10 Litres / 2.6 USG
Electrical Circuit	
Operating Voltage	12 Vcc
Alternator	85 Amp
Battery	70 Ah

Flailbot	Supreme Stage V / T4 Final (75hp)
Hydraulic System	
Displacement	Tandem piston pump with variable engine size and closed circuit
Displacement Capacity	154 Litres max @ 2750 rpm 40 USG max @ 2750 rpm
Displacement Pressure	400 Bar max
Services	Gear Pump
Services Capacity	15 Litres max @ 2750 rpm 4 USG max @ 2750 rpm
Services Pressure	200 Bar max
Tool	Closed Circuit Piston Pump
Tool Capacity	93 Litres max @ 2500 rpm 24.6 USG max @ 2500 rpm
Tool Pressure	380 Bar max
Oil Tank Capacity	72 Litres / 19 USG
Operating Oil Quantity	82 Litres / 22 USG
Controls	
Brand	Scanreco
Frequency	2.4 Ghz
Range Signal	150m / 492'
Battery	Rechargeable



Shredding head

Fitted as standard with 1650mm (5'5") shredding head and pushbar.

